

Subdivision of T. 30 S., R. 33 E., M. D. B. & M.

chs.

29.92 Tramway of Gold Peak Mining Co. bears S. 60° E.

30.80 Cross ravine, 8 lks. wide, course W., ascend.

40.00 Set a porphyry stone, 20x6x5 ins., 15 ins. in the ground,
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which
An oak, 28 ins. in diam., bears S. 37° 30' W., 12 lks.
dist., marked $\frac{1}{4}$ S 29 B.T.

An oak, 12 ins. in diam., bears N. 81° 30' E.,
100 lks. dist., marked $\frac{1}{4}$ S 28 B. T.

45.55 Trail to Gold Peak Mine bears W. and SE.

46.55 Top of saddle in spur, bears W. and descend.

53.00 Cross ravine, 15 lks. wide, course NW.

59.27 Cross ravine, 10 lks. wide, course NW.

60.28 Cross ravine, 20 lks. wide, course W.

67.70 Top of ^{Spur} spur, bears NW. descend.

78.10 Cross ravine, 6 lks. wide, course SW.

79.00 Cross ravine, 10 lks. wide, course SW.

80.00 Set a granite rock, 26x8x7 ins., 19 ins. in the ground
for cor. of secs. 20, 21, 28 and 29, marked with 2
notches on S. and 4 notches on E. edge, from which
An oak, 8 ins. in diam., bears N. 37° 50' E.,
97 lks. dist., marked T 30 S R 33 E S 21 B.T.
An oak, 10 ins. in diam., bears S. 79° E.,
77 lks. dist., marked T 30 S R 33 E S 28 B.T.
An oak, 10 ins. in diam., bears S. 14° W.,
72 lks. dist., marked T 30 S R 33 E S 29 B.T.
An oak, 10 ins. in diam., bears N. 2° W.,
73 lks. dist., marked T 30 S R 33 E S 20 B.T.

Land mountainous.

Soil, rocky and thin. 2nd and 3rd rate.

Timber, scattering oaks, underbrush, buckeye and scruboak.

Mountainous land and exceptionally difficult to survey

on account of steep slopes, dense undergrowth and

loose soil, 80.00 chs.